

PRESSMAX

XtraMax System Cleaner F15

CLEANING CONCENTRATE FOR USE IN DAMPENING SYSTEMS

Key Characteristics

- ✓ 5 - 20 % dosage
- ✓ 3 - 4 hrs circulation time
- ✓ PH neutral
- ✓ Not foaming

Directions for use

Mix 5 - 20 % with pure water, depending on the grade of pollution. Let this solution circulate through the dampening system for 3 - 4 hours, after it has been drained from the fountain solution. Improve the cleaning power by using warm water. Then drain off the cleaning solution and rinse the system several times with pure water, before refilling with fresh fountain solution.

Transport and storage

Protect against extreme weather conditions. Do not store at temperature above 35 °C or below -10 °C. Take necessary precautions to avoid environment pollution due to accidental leakage.

Packaging

- 12 x 1 L plastic bottles
- 4 x 5 L plastic drum
- 25 L plastic drum
- 200 L plastic drum

Features and benefits

Strong cleaning action

- ✓ Less standstills of system.
- ✓ Economical in use.

Corrosion inhibited

- ✓ No attack of system parts.

Neutral product

- ✓ No influence on the pH of the dampening solution that it used after the cleaning
- ✓ Fast restart after cleaning
- ✓ No foaming tendency

FUJIFILM